



ROTARY HEAT SEALERS



TS 45D
TS 45DN

Enjoy quality at a small price

The **TS 45D** range is particularly suitable for small sterilization units such as **dental** and medical centers, laboratories, ...

The **TS 45D** key strengths:

- A handy, compact, solid and reliable range
- An excellent sealing quality for all sealable pouches & reels
- Standards : CE, EN 868-5, ISO 11607-2 (N)
- Made in France





TS 45D sealer with stainless steel support tray



TS 45 sealer

	TS 45D	TS 45DN
TECHNICAL CHARACTERISTICS		
Type : Rotary heat sealer	✓	✓
Standards : CE / CEM	✓	✓
Standards : EN 868-5, DIN 58953-7	✓	✓
Standards : EN ISO 11607-2	-	✓
Calibration certificate (COFRAC att.)	optional	optional
Microprocessor control	✓	✓
Display	1 line LCD	1 line LCD
Temperature range	20-230°C	20-230°C
Temperature regulation tolerance	2%	2%
Automatic motor start & stop by photocell	✓	✓
Safety: automatic start-up at set point	✓	✓
Safety : overheating automatic stop (250°C)	✓	✓
Safety : critical parameters control complying with ISO 11607-2 standard (temperature & pressure)	-	✓
Safety : automatic stop if critical parameters exceed limits	-	✓
Fixed pouches guide	✓	✓
Sealing width	15mm	15mm
Sealing length	unlimited	unlimited
Sealable pouches (SBS) : steam / OE / alu / Tyvek® ...	✓	✓
Main connection / frequency	230V - 50/60 Hz	230V - 50/60 Hz
Power	400 W max.	400 W max.
Hood / cover	stainless steel	stainless steel
Dimensions L x l x H (mm)	440 x 250 x 140	440 x 250 x 140
Weight (Kg)	8	8

ACCESSORIES

Stainless steel front support tray (580 x 160 x 50 mm)	optional	optional
Roll conveyor (800 x 300 x 50 mm)	optional	optional